## **Integrated Base Sounder**



## **Product Information**

The Integrated Base Sounder comprises a base sounder with integral mounting base, and is designed for indoor use with Discovery and XP95 detectors.

- · Choice of two tones
- Choice of two volume ranges 55-75 dB(A) and 75 91 dB(A)
- An 'emergency signal' tone to DIN 33404 Part 3 and discretionary constant tone for non-fire emergency use.
- · Individual and group addressing
- · Synchronisation of 'DIN' and 'constant' tones
- Unique acoustic self-test
- Available with or without built-in isolator
- Available with 'slow whoop' tone to Dutch standard NEN2575

## **Product Overview**

Product Integrated Base Sounder - with Isolator Product Integrated Base Sounder - DIN tone with Isolator

Part No. 45681-277 Part No. 456814-300

Product Integrated Base Sounder - non-isolated Product Base Cap - White

Part No. 45681-278 Part No. 45681-292

Product Integrated Base Sounder - Slow Whoop - with Isolator Product Base Cap - Red

Part No. 45681-290 Part No. 45681-293

Product Integrated Base Sounder - Slow Whoop

Part No. 45681-291

## Technical data

All data is subject to change without notice. Specifications are typical at 24 V,  $23^{\circ}$ C and 50% RH unless otherwise stated.

Supply voltage 17 V - 28 V dc Protocol pulses 5 V - 9 V

Current consumption at 24 V

Switch-on surge < 1 s 1.2 mA

Quiescent 1.2 mA

Quiescent - DIN tone sounder 200 μA

Sounder operated 5 mA

Maximum sound output at 90° 91 dB(A)

Maximum sound output to EN54 83 dB(A)

Sound pressure level data is published in PP2203 available upon request from Apollo

Operating temperature - 20°C to +60°C

Humidity (no condensation) 0 - 95%

IP rating IP21D

**Dimensions** 115 mm diameter x 38 mm depth

Weight 140 g

36 Brookside Road, Havant, Hampshire PO9 1JR, UK.

Tel: +44 (0)23 9249 2412 Fax: +44 (0)23 9249 2754

Email: sales@apollo-fire.com Web: www.apollo-fire.co.uk







